




Liune



SOCKET OUTLET INSTALLATION IN LIUNE LEMENT

SOCKET OUTLET INSTALLATION



Possible electric drafts








Drill a hole in the drywall with a hole saw AT5 (Ø 74 mm).

FEATURES OF ELECTRICAL FIXTURES FOR VARIOUS ELEMENTS AND DOORS		
BODY THICKNESS mm	DOOR mm	SOCKET PLACED IN THE ELEMENT
66	25 to 32	Surface
95	25	Recessed base
95	32 to 40	Surface
120	25	Recessed
120	32 to 40	Recessed sbase

SOCKET OUTLET INSTALLATION

PLATE-MOUNTS DIMENSIONS





Mounting box




PLATE- MOUNT 12–13 mm

With the plate- mounts you attach the flush-mounted box to the plasterboard.

Install the plate mounts on opposite sides of the hole (PMR 784) (2 pcs.)







3 INSTALL OUTLET IN PLACE.

Flush-mounted box (PMR 859) 38 mm to 95 mm frame when door 25 mm.

The mounting box is inserted into the plate mounts from the back side of the plasterboard, thereby locking the flush-mounting box into the wall. The protector is removed from the box during attachment.

The mounting box is attached to the grooves in the plate mounts and holds the box tightly in place.



Manufacture and sale of Liune:

Aulis Lundell Ltd Tel. 020 7341 400

myynti@liune.fi • info@liune.fi www.liune.fi





EPD No. RTS_38_19 LIUNE -door system with glass/MDF door www.liune.fi/epd



Liune door is manufactured in accordance with the ISO 9001:2015 quality system and current regulations and regulations from CE marked profiles.



Operations in accordance with $\,the\,$ environmental management system have been in accordance with

Liune Door is patented in the EU and Norway, as well as in the USA.





BORROWING THE IMAGES IN THE INSTRUCTIONS IS ONLY ALLOWED FOR AULIS LUNDELL OY'S CUSTOMERS AND PARTNERS WHEN THE SOURCE IS MENTIONED. **IMAGES AND** WE RESERVE THE RIGHT TO MAKE CHANGES TO RELATED TEXTS.



www.liune.fi









